

Part #: 100-00275-01

Description

The MEA-2410-SMA connector mount Antenna is a low profile antenna solution, with a very high-performance ideal for maintaining constant network connectivity. The MEA-2410-SMA covers all WiFi, BT, ZigBee, and ISM standard frequencies. This is an ideal antenna for telematics systems, remote surveillance, asset tracking and any IOT system applications. The MEA-2410-SMA is easy to install with maximum durability offering IP67 rated housing and anti-rotation mounting. The high performance and low profile make this antenna ideal for the most challenging installations.



Electrical Specification

Parameter	Specification	
Frequency Range	2410-2490 MHz	4920-5925MHz
Band	2.4 GHz	5.0GHz
Return Loss	-14.7 dB	-12.8 dB
VSWR	1.4:1	1.7:1
Efficiency	60%	83%
Peak Gain	4.0 dBi	5.2 dBi
Average Gain	-2.2 dB	-0.9 dB
Impendance	50 Ω	
Polarization	Linear	
Radiation Pattern	Omni-Directional	
Max Input Power	25 W	

Mechanical Specification

Parameter	Specification
Antenna Dimensions	Ø 10 x 56 mm
Operating Temperature	-40°C to + 85°C
Mounting Type	Connector Mount
Connector	Most RF Connectors
Radome/Color	ABS UV Stable/ Black
Substance Compliance	RoHS

*Mounted on Ground Plane 70 x 35 cm

Features

- 2.4/5.0 GHz ISM, 2410-2490MHz, 4920-5925MHz
- · Easy mounting: Connector Mount
- · High Gain
- Dimensions Ø 10 x 56 mm

Applications

- WIFI applications
- · Navigation and telematics systems
- IoT applications
- · Automotive connectivity
- Multimedia
- Fleet management
- · HD video and audio streaming















